



- ▶ High performance
- ▶ Transfer duty specification
- ▶ Quality and reliability
- ▶ Suitable for major industrial and commercial installations, civic amenity sites, and small transfer stations
- ▶ Cost-efficient throughput and excellent compaction when operated in conjunction with a 50cu yard container
- ▶ Comprehensive range of loading options available
- ▶ Prompt after sales service

MACHINE SPECIFICATIONS

400	CHARGE BOX VOLUME (NOM)	3.75 cu yd	2.90 m ³	THEORETICAL THROUGHPUT/HOUR	187 cu yd	143 m ³
	MACHINE LENGTH	170 ins	4335 mm	COMPACTION FORCE	88514 lbs	40150 kg
	MACHINE WIDTH	68.5 ins	1740 mm	ELECTRIC MOTOR	20 hp	15 kw
	STANDARD LOADING HEIGHT	51 ins	1295 mm	HYDRAULIC CYLINDER	7" dia	175 mm dia
	CYCLE TIME	46 sec		PUMP CAPACITY	14 gpm	64 l/m
500	CHARGE BOX VOLUME (NOM)	4.5 cu yd	3.45 m ³	THEORETICAL THROUGHPUT/HOUR	237 cu yd	181 m ³
	MACHINE LENGTH	197 ins	5010 mm	COMPACTION FORCE	88514 lbs	40150 kg
	MACHINE WIDTH	68.5 ins	1740 mm	ELECTRIC MOTOR	30 hp	22 kw
	STANDARD LOADING HEIGHT	51 ins	1295 mm	HYDRAULIC CYLINDER	7" dia	175 mm dia
	CYCLE TIME	42 sec		PUMP CAPACITY	18 gpm	82 l/m
600	CHARGE BOX VOLUME (NOM)	6.15 cu yd	4.70 m ³	THEORETICAL THROUGHPUT/HOUR	361 cu yd	276 m ³
	MACHINE LENGTH	264 ins	6710 mm	COMPACTION FORCE	110584 lbs	50160 kg
	MACHINE WIDTH	68.5 ins	1740 mm	ELECTRIC MOTOR	30 hp	22 kw
	STANDARD LOADING HEIGHT	51 ins	1295 mm	HYDRAULIC CYLINDER	8" dia	200 mm dia
	CYCLE TIME	40 sec		PUMP CAPACITY	*50 gpm	227 l/m

400 and 500 special models are available with uprated single cylinder (SP50) twin cylinder (T) or increased throughput (S) and (HS).
600 special models available on request. We reserve the right to amend specification without prior notice.

* Two stage pump

Kelpack

Station Works, Station Road, Ecclesfield, Sheffield S35 9YR

Telephone: 0114 246 8679 Email: info@kelpack.com

Fax: 0114 240 2601 Web: www.kelpack.com

Kelpack is a trading name of Kelwick Engineering Ltd.

